

FEATURES	
※ 200-240V AC input only	※ Constant voltage design
※ Can be installed on DIN Rail TS-35/7.5 or 15	※ DC ok signal (Open collector type)
※ Short circuit protection	※ Over load protection
※ Over voltage protection	※ Over temperature protection

INPUT	
Input range	200~240VAC
Input frequency	47 ~ 63 Hz
Inrush current	40A at 230VAC cold start at 25°C
Input current	0.7A/ 230VAC
Leakage current	<1.5mA at 50/60Hz 240VAC INPUT

OUTPUT					
Model number	DIN60W05	DIN60W12	DIN60W15	DIN60W24	DIN60W48
Output voltage	5Vdc	12Vdc	15Vdc	24Vdc	48Vdc
Output current	8A	5A	4A	2.5A	1.25A
Rated output power	40W	60W	60W	60W	60W
Output load efficiency	80%	82%	82%	83%	83%
Ripple & noise	100mV _{P-P}	150mV _{P-P}	150mV _{P-P}	200mV _{P-P}	300mV _{P-P}
Adjustment range	15%				
Hold-up time	110ms at full load and 230VAC nominal line				
Setup, Rise Time	max. 460ms, max. 30ms / 230VAC at full load				
Line Regulation	± 1%				
Load Regulation	± 1%				

SAFETY AND EMC REGULATIONS	
Safety Standards	Compliance to EN62368-1
Withstand Voltage	IN/OUT: 3kVAC, IN/GND: 2kVAC, OUT/GND: 0.5kVAC
EMC Emission	Compliance to EN55032
EMC Immunity	Compliance to EN55035

ENVIRONMENTAL	
Operating temp.	-20°C to 50 °C ambient derate each output at 4.0% per degree from 50°C to 60°C
Storage temp.	- 40 °C to +85 °C
Operating humidity	5% to 95% (non-condensing)
MTBF	200,000 hours at full load and 25 °C ambient conditions (demonstrated)
Dimensions	78 x 93 x 56mm

MECHANICAL SPECIFICATION

